

# RUSTPROTEC M30

## Product Description

RUSTPROTEC M30 is an oil film type rust preventive product which contains rust inhibitor additive. It is suitable for up to 3 months rust prevention. Moreover, honing and grinding lubrication of metal parts can be well applied.

## Benefits

- Good anti-rust and anti-corrosion properties even under high humidity condition
- Offers up to 3 months rust protection

## Applications

- Suitable for preventing rust on metal surface via dipping and brushing
- Provide anti-rust prevention at least 1 month and up to 3 months if store in shade and under low humidity atmosphere

*The Moving Innovation* 

# RUSTPROTEC M30

## Typical Characteristics

Tests	Methods	Units	Results
Color	ASTM D1500		1.5
Viscosity at 40 °C	ASTM D445	mm <sup>2</sup> /s	9.562
Density at 15 °C	ASTM D4052	kg/L	0.8380
Flash Point	ASTM D92	°C	168
Pour Point		°C	-27
Copper Strip Corrosion	ASTM D130		1a
Film Thickness	Film weight	Micron	5.9
Humidity Cabinet	ASTM D1748	Day	>30

## Caution

Workpieces must be totally dried before coating rust preventive oil especially ones which are previously cut by using water soluble coolant.

## Health and Safety

This product shows no significant health or safety hazard when used under the recommended applications and suitable handling.

Avoid the direct contact. Wash immediately after contact. Health and safety information is available on the Safety Data Sheet (SDS) which can be obtained from <http://pttlubricants.pttor.com>

**PTT LUBE SOLUTIONS** Professional Lubricant Service Partner



The product can cause some skin irritation and has flash point higher than 93.4°C

Note: Data and information contained in this publication are based on standard test under laboratory conditions and/or performance test. To consider the use of PTT Lubricants' products in particular application, customer is responsible for determining whether product and information are appropriate for customer conditions or should consult with PTT Lubricants' technical service division. The procedure of using any lubricant may differ or change depended on different machines and their manuals. Therefore, we recommend to read, understand and review the latest SDS in order to ensure the use of product is accomplished safety.

The Moving Innovation 