

TERBIN T

ISO VG 32, 46, 68, 100

Product Description

Premium industrial turbine oils produced from high quality hydrocarbon basestocks and additive package to enhance oil drain interval, water separability and foam formation protection. TERBIN T is officially approved by SIEMENS.

Benefits

- Enhanced oxidative and thermal resistance to extend oil drain periods.
- Enhanced wear and corrosion protection.
- Highly effective antifoam protection.

Applications

- Recommended for water, steam, and gas turbines.
- Suitable for various applications e.g. hydraulic control systems, vacuum pump, and general transmission systems where vanish protection, and rust and oxidation prevention are required.
- Especially designed for turbines that requires SIEMENS standard.

The Moving Innovation 

TERBIN T

ISO VG 32, 46, 68, 100

Typical Characteristics

Tests	Methods	Units	Results			
			32	46	68	100
Kinematic Viscosity at 40 °C	ASTM D 445	mm ² /s	33.20	47.10	68.98	97.55
Kinematic Viscosity at 100 °C	ASTM D 445	mm ² /s	5.58	6.84	8.82	11.23
Viscosity Index	ASTM D 2270		112	104	103	96
Density at 15°C	ASTM D 4052	g/cm ³	0.856	0.863	0.872	0.876
Flash Point (COC)	ASTM D 92	°C	235	244	250	264
Pour Point	ASTM D 97	°C	-18	-9	-9	-9
Total Acid Number	ASTM D 664	mgKOH/g	0.14	0.15	0.15	0.15
Rust Prevention	ASTM D 665		Pass	Pass	Pass	Pass
Air Release Property at 50°C	ASTM D3427	min	3	5	6	7
Oxidation Stability	ASTM D 943					
Time to 2.0 TAN		hr	>10,000	>10,000	>10,000	>10,000
Copper strip corrosion, 3hr at 100°C	ASTM D 130		1a	1a	1a	1a

Performance Standards

- DIN 51515 Part 1 (L-TD)
- DIN 51524 Part 1 (HL)
- General Electric GEK 32568 F
- Siemens/KWU TLV 9013 04, 9013 05
- BS 489 (CIGRE)
- ALSTOM HTGD 90117 V0001 U

Health and Safety

This product shows no significant health or safety hazard when used under the recommended applications and suitable handling.

Avoid the direct contact. Wash immediately after contact. Health and safety information is available on the Safety Data Sheet (SDS) which can be obtained from <http://pttlubricants.pttplc.com>

PTT LUBE SOLUTIONS Professional Lubricant Service Partner



The product can cause some skin irritation and has flash point higher than 93.4°C

Note: Data and information contained in this publication are based on standard test under laboratory conditions and/or performance test. To consider the use of PTT Lubricants' products in particular application, customer is responsible for determining whether product and information are appropriate for customer conditions or should consult with PTT Lubricants' technical service division. The procedure of using any lubricant may differ or change depended on different machines and their manuals. Therefore, we recommend to read, understand and review the latest SDS in order to ensure the use of product is accomplished safety.

The Moving Innovation 